










3-A Aseptic and Reducing N7 Valves

The N7 Aseptic rising stem compression-type valve series meets the requirements of 3-A Sanitary Standards. Clean-in-place and aseptic models are available in shut-off with standard choice of weld or tri-clamp connections. All models of N7 automated air-actuated compression-type valves are available in 1", 1 1/2", 2", 2 1/2" and 3" sizes. Recent additions to this product line include aseptic pressure reducing valve models and the option of DIN 11864 and ACME threaded type connections in place of standard connections to serve the changing needs of our customers!

Main features	<ul style="list-style-type: none"> 3-A Aseptic Standards Open or closed positions visually detectable Field reversible actuator Visual leak detection through open yoke design Reducing type with spring control or Air control Maximum operating temperature 280°F (140°C)
Industry for use	Dairy, Food and Beverage
Connections	<ul style="list-style-type: none"> Any combination of clamp, threaded or weld ends are available Two 1/8" ISO actuator connections
Options	<ul style="list-style-type: none"> High temperature and/or pressure valves available on request. Microswitch unit with waterproof cover Mechanical switches Honeywell type 5 SEI Proximity switches Honeywell type 922 FSI 1.5 – A9P – SE Solenoid valves Honeywell Lucifer type 131M 75.50.8993.488980 Magnetic / electronic feedback unit with automatic calibration Magnetic / electronic feedback unit with solenoid control and automatic calibration
Materials	<ul style="list-style-type: none"> Product contact parts grade 316 stainless steel Valve seat material: PTFE O-ring material: EPDM PC



3A Aseptic Air actuated N701 valve - Weld / Weld				Basic					Max. Working Pressure		
				Part number	Size	L	W	H	A	D	Bar / Psi
  	A1-001-AA	1"	52	52	327	88	25,4x1,5	6 / 90			
	A1-112-AA	1,5"	52	52	320	88	38,2x1,7	6 / 90			
	A1-002-AA	2"	64	64	350	113	52x2	6 / 90			
	A1-212-AA	2,5"	75	75	427	140	64x2	6 / 90			
	A1-003-AA	3"	85	85	452	140	77x2	4 / 60			
3A Aseptic Air actuated N702 valve - Weld / Weld / Weld				Basic					Max. Working Pressure		
				Part number	Size	L	W	H	A	D	Bar / Psi
  	A2-001-AAA	1"	52	52	327	88	25,4x1,5	6 / 90			
	A2-112-AAA	1,5"	52	52	320	88	38,2x1,7	6 / 90			
	A2-002-AAA	2"	64	64	350	113	52x2	6 / 90			
	A2-002-AAA	2,5"	75	75	427	140	64x2	6 / 90			
	A2-003-AAA	3"	85	85	452	140	77x2	4 / 60			
3A Aseptic Reducing valve - Weld / Weld				Basic					Max. Working Pressure		
				Part number	Size	L	W	H	A	D	Bar / Psi
  	AR-001-AA	1"	52	52	327	88	25,4x1,5	6 / 90			
	AR-112-AA	1,5"	52	52	320	88	38,2x1,7	6 / 90			
	AR-002-AA	2"	64	64	350	113	52x2	6 / 90			
	AR-212-AA	2,5"	75	75	427	140	64x2	6 / 90			
	AR-003-AA	3"	85	85	452	140	77x2	4 / 60			